

## Tyre Label Perm

### Product Code

TYRE

### Product Details

A semi gloss paper laminated to a 7 micron aluminium barrier foil.  
This paper provides excellent print quality by all the usual printing techniques including thermal transfer.

### Face Material

Description  
Finish and Colour  
Weight / Thickness

Coated paper  
Semi gloss White  
100 gsm / 80 micron

### Adhesive

Type  
Minimum Application Temp  
In Service Temp  
Initial Tack  
Ultimate Adhesion  
Notes

Extra Permanent, Hot Melt  
0 °C  
-20 °C to +60 °C  
Very High  
Very High  
Complies with requirements of indirect food additive regulation 21 CFR-175.105  
“Adhesive” The complies with the Bfr XIV regulations for direct contact with dry  
and moist non-fatty foodstuffs ISEGA certificate No. 31790 U 11

### Release Liner

Weight  
Colour  
Thickness

62 gsm  
Honey glassine  
55 micron

### Application

Tyres, Fruit labelling, Metal Detectable applications and other applications include rough, contoured surfaces.

### Shelf Life

1 year

We reserve the right to supply comparable materials against any product without prior notice. The values given are typical, the information being given in good faith but without warranty. All goods are supplied in accordance with our Standard Terms and Conditions of Sale, and no recommendations for specific application or use are given. The user must satisfy themselves as to the suitability of a particular grade for their own application.