

Demand Jet Gloss C2075 Deep Freeze

Product Code FDJGC2075

Product Details A white, high gloss, coated paper with a micro-porous and absorbent surface Structure specifically designed for waterbased ink jet printing. It can also be printed by conventional technologies, we recommend Flexo for best results using low viscosity inks, the ink absorbent consumption may be high due to The nature of the facestock.

Face Material

Description Coated paper
Finish and Colour High Gloss White
Weight / Thickness 85 gsm / 101 micron

Adhesive

Type C2075, Permanent, Rubber
Minimum Application Temp -20 °C
In Service Temp -50 °C to +70 °C
Initial Tack High
Ultimate Adhesion High
Notes The adhesive can be used in direct contact with dry and moist, non-fatty Foodstuffs. Specially designed for use at low temperature and freezer conditions. Complies with the European Food Directives FDA 175.105 and German recommendations XIV as published by BfR.

Release Liner

Weight 61 gsm
Colour BG40 White, supercalendered glassine
Thickness 54micron

Application

The high ink hold out and quick drying provides for excellent clarity and density of printed graphics, making it the perfect choice for primary and secondary packaging labels.

Shelf Life

2 years

We reserve the right to supply comparable materials against any product without prior notice. The values given are typical, the information being given in good faith but without warranty. All goods are supplied in accordance with our Standard Terms and Conditions of Sale, and no recommendations for specific application or use are given. The user must satisfy themselves as to the suitability of a particular grade for their own application.