



Specification

50mic Gloss Clear Acetate Perm

Product Code 50CAP

Product Details A gloss clear cellulose acetate film suitable for flexographic, letterpress, gravure, hotfoil and offset litho processes. Can also be used for thermal transfer applications.

Face Material

Description Acetate film
Finish and Colour Gloss Clear
Weight / Thickness 50 gsm / 65 micron

Adhesive

Type Permanent, Acrylic
Minimum Application Temp 5 °C
In Service Temp -10 °C to 80 °C
Initial Tack High
Ultimate Adhesion Very High
Notes Conforms with regulations for direct contact with dry, moist and such kind of fatty foodstuffs which have a reduction factor of at least 3 according to the EC Directive 85/572/CEE (ISEGA certificate no. 29957 U 10)

Release Liner

Weight 62 gsm
Colour Honey glassine
Thickness 55 micron

Application Cosmetics, toiletries & pharmaceutical work. Also suitable for medium level tamper evidence applications

Shelf Life 2 years

We reserve the right to supply comparable materials against any product without prior notice. The values given are typical, the information being given in good faith but without warranty. All goods are supplied in accordance with our Standard Terms and Conditions of Sale, and no recommendations for specific application or use are given. The user must satisfy themselves as to the suitability of a particular grade for their own application.

Ref :- 142

t:0161 343 1131 w:www.magnum-uk.com e:sales@magnum-uk.com

MAGNUM MATERIALS LTD, THE SELF ADHESIVE CENTRE Globe Lane Industrial Estate, Dukinfield, Cheshire SK16 4UG