



# Specification

## 7871EC Gloss White Polyester TT Perm

**Product Code** 7871EC

### Product Details

A gloss white polyester film which is top coated for thermal transfer printing. The top coat also provides improved ink anchorage for traditional forms of printing.  
UL and cUL approved MH18072

### Face Material

Description Polyester film  
Finish and Colour Gloss White  
Weight / Thickness --- / 50 micron

### Adhesive

Type 350E, Permanent, Acrylic  
Minimum Application Temp Room temperature or higher.  
In Service Temp - 40 °C to 140 °C  
Initial Tack High  
Ultimate Adhesion Very high  
Notes Excellent adhesion, even on low surface energy substrates combined with excellent temperature and chemical resistance.

### Release Liner

Weight 62 gsm  
Colour White Densified Double Sided Glassine  
Thickness 56 micron

### Application

Barcode labels, rating plates, asset, warning, instruction, nameplate labels.

### Shelf Life

2 years

We reserve the right to supply comparable materials against any product without prior notice. The values given are typical, the information being given in good faith but without warranty. All goods are supplied in accordance with our Standard Terms and Conditions of Sale, and no recommendations for specific application or use are given. The user must satisfy themselves as to the suitability of a particular grade for their own application.

Ref :- 271

**t:0161 343 1131 w:www.magnum-uk.com e:sales@magnum-uk.com**

MAGNUM MATERIALS LTD, THE SELF ADHESIVE CENTRE Globe Lane Industrial Estate, Dukinfield, Cheshire SK16 4UG