



Specification

Radiant Red Litho Perm

Product Code RADRP

Product Details A woodfree Radiant (fluorescent) red coated paper.
Suitable for printing by flexo, letterpress and litho.
Suitable for thermal transfer printing.

Face Material

Description Paper
Finish and Colour Radiant Red
Weight / Thickness 75gsm / 76 micron

Adhesive

Type Permanent, Acrylic
Minimum Application Temp 5 °C
In Service Temp -10 °C to +70 °C
Initial Tack High
Ultimate Adhesion Very High
Notes Good for labelling difficult substrates such as polyethylene and carton board
Complies with FDA 175.105 indirect food contact

Release Liner

Weight 62 gsm
Colour Honey glassine
Thickness 54 micron

Application Product identification, promotional labels.

Shelf Life 1 year

We reserve the right to supply comparable materials against any product without prior notice. The values given are typical, the information being given in good faith but without warranty. All goods are supplied in accordance with our Standard Terms and Conditions of Sale, and no recommendations for specific application or use are given. The user must satisfy themselves as to the suitability of a particular grade for their own application.

Ref :- 043

t:0161 343 1131 w:www.magnum-uk.com e:sales@magnum-uk.com

MAGNUM MATERIALS LTD, THE SELF ADHESIVE CENTRE Globe Lane Industrial Estate, Dukinfield, Cheshire SK16 4UG