



Specification

Radiant Yellow Litho Peel

Product Code RADYR

Product Details Fluorescent, coated yellow woodfree paper.
Suitable for conventional printing methods such as letterpress, flexo and offset and thermal transfer.

Face Material

Description Fluorescent coated paper
Finish and Colour Matt Yellow
Weight / Thickness 73 gsm / 78 micron

Adhesive

Type Peelable, acrylic
Minimum Application Temp -15 °C
In Service Temp -30 °C to +80 °C
Initial Tack Low
Ultimate Adhesion Low
Notes Good UV resistance. Removes clean from many substrates. Not suitable for window labelling. Complies with FDA 175.105 and German recommendations XIV as published by BfR. Can be used in direct contact with dry, moist and such kind of fatty foodstuffs which have a reduction factor of at least 3.

Release Liner

Weight 57 gsm
Colour White Glassine
Thickness 51 micron

Application Labels for pricing, advertising and promotional uses.

Shelf Life 2 years

We reserve the right to supply comparable materials against any product without prior notice. The values given are typical, the information being given in good faith but without warranty. All goods are supplied in accordance with our Standard Terms and Conditions of Sale, and no recommendations for specific application or use are given. The user must satisfy themselves as to the suitability of a particular grade for their own application.

Ref :- 038

t:0161 343 1131 w:www.magnum-uk.com e:sales@magnum-uk.com

MAGNUM MATERIALS LTD, THE SELF ADHESIVE CENTRE Globe Lane Industrial Estate, Dukinfield, Cheshire SK16 4UG