



Specification

50mic Gloss White Polyester Perm

Product Code 50GWP

Product Details

A Gloss White polyester film surface treated.
This is an exceptionally white opaque film.
Suitable for letterpress uv, screenprinting uv, gravure, hot stamping and thermal transfer.
UL APPROVED MH18669

Face Material

Description Polyester film surface treated
Finish and Colour Gloss White
Weight / Thickness 70 gsm / 50 micron

Adhesive

Type Permanent, Acrylic
Minimum Application Temp +10 °C
In Service Temp -30 °C to +120 °C
Initial Tack Medium
Ultimate Adhesion High
Notes Very good adhesion on glass and wide variety of substrates, except for apolar (PE, PP). BGVV compliance (indirect food contact).

Release Liner

Weight 90 gsm
Colour White Glassine, 1 side siliconised
Thickness 77 micron

Application

Labels for cosmetics, appliances, electrical equipment and instruments.

Shelf Life

2 years

We reserve the right to supply comparable materials against any product without prior notice. The values given are typical, the information being given in good faith but without warranty. All goods are supplied in accordance with our Standard Terms and Conditions of Sale, and no recommendations for specific application or use are given. The user must satisfy themselves as to the suitability of a particular grade for their own application.

Ref :- 044

t:0161 343 1131 w:www.magnum-uk.com e:sales@magnum-uk.com

MAGNUM MATERIALS LTD, THE SELF ADHESIVE CENTRE Globe Lane Industrial Estate, Dukinfield, Cheshire SK16 4UG