



Specification

50mic Matt Silver Polyester Comp Imp

Product Code 50MSPP

Product Details

A top coated matt silver polyester film. The top coating enables ink reception of most common printing methods and also is computer imprintable. Good resistance to many petroleum based solvents, high temperature, scratching and smudge.
UL APPROVED MH18079

Face Material

Description Polyester film
Finish and Colour Matt Silver
Weight / Thickness 56 gsm / 44 micron

Adhesive

Type Permanent, Acrylic
Minimum Application Temp 10 °C
In Service Temp - 20 °C to 130 °C
Initial Tack High
Ultimate Adhesion High
Notes Good resistance to chemicals and heat. BS5609 Marine Approved
Suitable for Indirect contact with foodstuffs (28886 U 09)

Release Liner

Weight 80gsm
Colour White Glassine
Thickness 68 micron

Application

Variable data, serial numbers, barcodes, product coding etc.
Electrical appliance, instruction panels, nameplates etc.

Shelf Life

2 years – When stored at 15-25 °C, (50+/-5) % relative humidity, in original packaging

We reserve the right to supply comparable materials against any product without prior notice. The values given are typical, the information being given in good faith but without warranty. All goods are supplied in accordance with our Standard Terms and Conditions of Sale, and no recommendations for specific application or use are given. The user must satisfy themselves as to the suitability of a particular grade for their own application.

Ref :- 037

t:0161 343 1131 w:www.magnum-uk.com e:sales@magnum-uk.com

MAGNUM MATERIALS LTD, THE SELF ADHESIVE CENTRE Globe Lane Industrial Estate, Dukinfield, Cheshire SK16 4UG