



Specification

60mic Gloss White PP TC Peel

Product Code 60GPR

Product Details

A Gloss White bi-oriented polypropylene film with top coating.
The coating gives very good ink key, has a good scratch resistance.
Suitable for letterpress uv, screenprinting uv, gravure and hot stamping.

Face Material

Description Polypropylene film with top coating
Finish and Colour Gloss White
Weight / Thickness 46 gsm / 60 micron

Adhesive

Type Peelable, Acrylic
Minimum Application Temp +15 °C
In Service Temp -5 °C to +60 °C
Initial Tack Low
Ultimate Adhesion Low
Notes Good long term removability from a wide variety of surfaces
Complies with regulations for direct contact with dry, moist and such
Kind of fatty foodstuffs which have a reduction factor of at least 2
According to EC directive 85/572/CEE (ISEGA certificate No. 30229 U 10)

Release Liner

Weight 80 gsm
Colour White Glassine
Thickness 68 micron

Application

Multipurpose removable labels for industrial use

Shelf Life

2 years

We reserve the right to supply comparable materials against any product without prior notice. The values given are typical, the information being given in good faith but without warranty. All goods are supplied in accordance with our Standard Terms and Conditions of Sale, and no recommendations for specific application or use are given. The user must satisfy themselves as to the suitability of a particular grade for their own application.

Ref :- 142

t:0161 343 1131 w:www.magnum-uk.com e:sales@magnum-uk.com

MAGNUM MATERIALS LTD, THE SELF ADHESIVE CENTRE Globe Lane Industrial Estate, Dukinfield, Cheshire SK16 4UG