



# Specification

## 60mic Gloss White PP TC Perm BS5609

**Product Code** 60GWPP

**Product Details** Gloss white top coated cavitated polypropylene.  
Printable with UV Flexo, UV Offset, UV Letterpress, UV Screenprinting, Gravure and Hot stamping. Overvarnishing is recommended to improve scratch and chemical resistance.

### Face Material

Description Top coated cavitated  
Finish and Colour Gloss White  
Weight / Thickness 45 gsm / 60 micron

### Adhesive

Type Permanent, Rubber based  
Minimum Application Temp 0 °C  
In Service Temp -20 °C to +70 °C  
Initial Tack Very High  
Ultimate Adhesion Very High  
Notes Suitable for rough and apolar (PE & PP) substrates.  
ISEGA approved (Direct contact dry & moist, non fatty foodstuffs).

### Release Liner

Weight 62 gsm  
Colour White Glassine, 1 side siliconised  
Thickness 54 micron

### Application

Top coating and adhesive are fully compliant with food industry requirements.  
Not recommended for fan folder tags.

### Shelf Life

2 years

We reserve the right to supply comparable materials against any product without prior notice. The values given are typical, the information being given in good faith but without warranty. All goods are supplied in accordance with our Standard Terms and Conditions of Sale, and no recommendations for specific application or use are given. The user must satisfy themselves as to the suitability of a particular grade for their own application.

Ref :- 044

**t:0161 343 1131 w:www.magnum-uk.com e:sales@magnum-uk.com**

MAGNUM MATERIALS LTD, THE SELF ADHESIVE CENTRE Globe Lane Industrial Estate, Dukinfield, Cheshire SK16 4UG