



# Specification

## 60mic Matt White PET Laser Perm

**Product Code** 60MWPKP

### Product Details

A matt White polyester film with a top coating for better printability. The matt surface offers an excellent quality of the imprint by screen, letterpress and flexo printing. Also suitable for thermal transfer and laser printers after production.

### Face Material

Description Polyester film  
Finish and Colour Matt White  
Weight / Thickness 75 gsm / 60 micron

### Adhesive

Type Permanent, Acrylic  
Minimum Application Temp 0 °C  
In Service Temp -40 °C to 150 °C  
Initial Tack Very High  
Ultimate Adhesion Very High  
Notes Very good resistant to light, heat and ageing. BS5609 Approved  
Complies with recommendation FDA 21 CFR 175.105

### Release Liner

Weight 64 gsm  
Colour White Glassine  
Thickness 56 micron

### Application

Particularly suitable for critical surfaces such as cardboard and ampoules. Perfect for applications that have to be resistant to high temperature and moisture surroundings.

### Shelf Life

2 years

We reserve the right to supply comparable materials against any product without prior notice. The values given are typical, the information being given in good faith but without warranty. All goods are supplied in accordance with our Standard Terms and Conditions of Sale, and no recommendations for specific application or use are given. The user must satisfy themselves as to the suitability of a particular grade for their own application.

Ref :- 240

**t:0161 343 1131 w:www.magnum-uk.com e:sales@magnum-uk.com**

MAGNUM MATERIALS LTD, THE SELF ADHESIVE CENTRE Globe Lane Industrial Estate, Dukinfield, Cheshire SK16 4UG