



# Specification

## 60mic Matt White PP TC Perm

**Product Code** 60MWPP

**Product Details** A matt white, top coated polypropylene film.  
Suitable for use with a variety of printing techniques. Variable information can be added by thermal transfer, dot matrix and inkjet. However, it is the Customer's responsibility to ensure that suitable ink and ribbon systems are being used.

### Face Material

Description Polypropylene film  
Finish and Colour Matt White  
Weight / Thickness 47 gsm / 66 micron

### Adhesive

Type Permanent, Acrylic  
Minimum Application Temp 0 °C  
In Service Temp -20 °C to 60 °C  
Initial Tack High  
Ultimate Adhesion High  
Notes The adhesive may stand in direct contact with dry, moist, and such kind of fatty foodstuffs to which a correction factor of at least 5 can be applied according to the commission regulation (EU) No. 10/2011. The adhesive is compliant to FDA 175.105

### Release Liner

Weight 60 gsm  
Colour White Glassine, one sided siliconised  
Thickness 53 micron

### Application

Cosmetics, toiletries, automotive lubricants and household chemicals requiring Durability and resistance to moisture and chemicals.

**Shelf Life** 1 year

We reserve the right to supply comparable materials against any product without prior notice. The values given are typical, the information being given in good faith but without warranty. All goods are supplied in accordance with our Standard Terms and Conditions of Sale, and no recommendations for specific application or use are given. The user must satisfy themselves as to the suitability of a particular grade for their own application.

Ref :- 057

**t:0161 343 1131 w:www.magnum-uk.com e:sales@magnum-uk.com**

MAGNUM MATERIALS LTD, THE SELF ADHESIVE CENTRE Globe Lane Industrial Estate, Dukinfield, Cheshire SK16 4UG