



# Specification

## 25mic Gloss Clear Polyester AL170

**Product Code** F25GCPAL170

**Product Details** A crystal clear, gloss overlaminating polyester film with print treated surface  
For enhanced ink adhesion.  
UL APPROVED MH27538

### Face Material

Description Polyester film  
Finish and Colour Gloss Clear  
Weight / Thickness 32 gsm / 25 micron

### Adhesive

Type AL170, Permanent, transparent, solvent based acrylic – Coat weight 20 g/sqm  
Minimum Application Temp 0 °C  
In Service Temp -80 °C to +150 °C  
Initial Tack Good  
Ultimate Adhesion High  
Notes High ageing stability. Very high resistance against heat and chemicals.

### Release Liner

Weight 80gsm  
Colour HF80 White, siliconized hygroflat backing.  
Thickness 78 micron

### Application

Is suitable for overlaminating films or papers providing durable labels with high Gloss, good abrasion and chemical resistance.

### Shelf Life

2 years

We reserve the right to supply comparable materials against any product without prior notice. The values given are typical, the information being given in good faith but without warranty. All goods are supplied in accordance with our Standard Terms and Conditions of Sale, and no recommendations for specific application or use are given. The user must satisfy themselves as to the suitability of a particular grade for their own application.

Ref :- 038

**t:0161 343 1131 w:www.magnum-uk.com e:sales@magnum-uk.com**

MAGNUM MATERIALS LTD, THE SELF ADHESIVE CENTRE Globe Lane Industrial Estate, Dukinfield, Cheshire SK16 4UG