



Specification

50mic Gloss White Polyester S8001

Product Code F50GWPS8001

Product Details A gloss white polyester film with a smooth surface which is covered with a topcoat for excellent ink anchorage. In addition to thermal transfer Printing the product can also be printed by all conventional methods such as Flexo, UV letterpress and Silkscreen. Specific testing is required.
UL APPROVED MH27538

Face Material

Description Polyester film
Finish and Colour Gloss White
Weight / Thickness 76 gsm / 50 micron

Adhesive

Type S8001, Permanent, Acrylic – Coat weight 27 g/sqm
Minimum Application Temp 5 °C
In Service Temp -40 °C to +150 °C
Initial Tack Good
Ultimate Adhesion High
Notes High ultimate adhesion onto a variety of substrates including apolar plastics and lacquers. It also offers good resistance to solvents and oils.

Release Liner

Weight 65gsm
Colour BG42 White, siliconized glassine paper, wood-free super calendered.
Thickness 58 micron

Application

Designed for labelling electronic, home appliance and other electrical Items due to its good bonding performance and low ooze.

Shelf Life

2 years

We reserve the right to supply comparable materials against any product without prior notice. The values given are typical, the information being given in good faith but without warranty. All goods are supplied in accordance with our Standard Terms and Conditions of Sale, and no recommendations for specific application or use are given. The user must satisfy themselves as to the suitability of a particular grade for their own application.

Ref :- 038

t:0161 343 1131 w:www.magnum-uk.com e:sales@magnum-uk.com

MAGNUM MATERIALS LTD, THE SELF ADHESIVE CENTRE Globe Lane Industrial Estate, Dukinfield, Cheshire SK16 4UG