



Specification

50mic Matt Silver Polyester AL170

Product Code F50MSPAL170

Product Details A matt silver polyester film. The surface has a matt topcoat. In addition to thermal transfer printing the product can also be printed by all conventional methods such as Flexo, UV letterpress and Silkscreen. Specific testing is required.

Face Material

Description Polyester film
Finish and Colour Matt Silver
Weight / Thickness 80 gsm / 55 micron

Adhesive

Type AL170, Permanent, transparent, solvent based acrylic – Coat weight 24 g/sqm
Minimum Application Temp 0 °C
In Service Temp -80 °C to +150 °C
Initial Tack Good
Ultimate Adhesion High
Notes High ageing stability. Very high resistance against heat and chemicals.

Release Liner

Weight 64gsm
Colour BG42 White, siliconized glassine paper, wood-free super calendered.
Thickness 57 micron

Notes

The adhesive meets the requirements of the so-called "Toy Standard" EN71-3. This product meets the requirements as stated in UL 969 and CSA C22.2 No. 0.15 for indoor and outdoor use. The UL file number is MH27538.

Application

Designed for labelling industrial products such as Nameplates and logistics labels.

Shelf Life

2 years

We reserve the right to supply comparable materials against any product without prior notice. The values given are typical, the information being given in good faith but without warranty. All goods are supplied in accordance with our Standard Terms and Conditions of Sale, and no recommendations for specific application or use are given. The user must satisfy themselves as to the suitability of a particular grade for their own application.

Ref :- 038

t:0161 343 1131 w:www.magnum-uk.com e:sales@magnum-uk.com

MAGNUM MATERIALS LTD, THE SELF ADHESIVE CENTRE Globe Lane Industrial Estate, Dukinfield, Cheshire SK16 4UG