



Specification

50mic Matt Chrome Polyester S8049

Product Code F50MSPS8049

Product Details

A matt metallic polyester film with a smooth surface which is covered with a topcoat for excellent ink anchorage. In addition to thermal transfer Printing the product can also be printed by all conventional methods such as Flexo, UV letterpress and Silkscreen. Specific testing is required.
UL APPROVED MH27538

Face Material

Description Polyester film
Finish and Colour Matt Chrome
Weight / Thickness 72 gsm / 50 micron

Adhesive

Type S8049, Permanent, Rubber – Coat weight 45 g/sqm
Minimum Application Temp 5 °C
In Service Temp -40 °C to +150 °C
Initial Tack Good
Ultimate Adhesion High
Notes High ultimate adhesion onto a variety of substrates including textured and and low surface energy substrates. Excellent chemical resistance. Briefly Repositionable and then adhesion increases to very high ultimate peel strength.

Release Liner

Weight 64gsm
Colour BG42 White, Both sides siliconized glassine paper, wood-free super calendered.
Thickness 55 micron

Application

Automotive industry labels. Labels to be supplied onto low surface energy Plastic automotive parts or other rough or low surface energy surfaces.

Shelf Life

2 years

We reserve the right to supply comparable materials against any product without prior notice. The values given are typical, the information being given in good faith but without warranty. All goods are supplied in accordance with our Standard Terms and Conditions of Sale, and no recommendations for specific application or use are given. The user must satisfy themselves as to the suitability of a particular grade for their own application.

Ref :- 038

t:0161 343 1131 w:www.magnum-uk.com e:sales@magnum-uk.com

MAGNUM MATERIALS LTD, THE SELF ADHESIVE CENTRE Globe Lane Industrial Estate, Dukinfield, Cheshire SK16 4UG