



# Specification

## Foamtac S2000N

### Product Code

FFT

### Product Details

A semi gloss white co-extruded product consisting of an expanded polystyrene layer with a clear polystyrene surface film.

Can be printed in the usual printing technologies; for variable information printing thermal transfer and inkjet can be used.

Handle with care; rough handling or scratching may leave permanent impressions in the relatively soft facestock.

### Face Material

Description

Co-extruded Polystyrene

Finish and Colour

Semi Gloss White

Weight / Thickness

54 gsm / 165 micron

### Adhesive

Type

S2000N, Permanent, Acrylic

Minimum Application Temp

0 °C

In Service Temp

-20 °C to +80 °C

Initial Tack

High

Ultimate Adhesion

Very High

Notes

The adhesive can be used in direct contact with dry, non fatty foodstuffs  
Complies with the European Food Directives FDA 175.105 and German  
Recommendations XIV as published by BfR.

### Release Liner

Weight

62 gsm

Colour

BG40 White, supercalendered glassine

Thickness

56 micron

### Application

Typical applications include product identical labels on packaging such as egg boxes, and other containers. Security labels.

### Shelf Life

2 years

We reserve the right to supply comparable materials against any product without prior notice. The values given are typical, the information being given in good faith but without warranty. All goods are supplied in accordance with our Standard Terms and Conditions of Sale, and no recommendations for specific application or use are given. The user must satisfy themselves as to the suitability of a particular grade for their own application.

Ref :- 038

**t:0161 343 1131 w:www.magnum-uk.com e:sales@magnum-uk.com**

MAGNUM MATERIALS LTD, THE SELF ADHESIVE CENTRE Globe Lane Industrial Estate, Dukinfield, Cheshire SK16 4UG