



# Specification

## LW60 S660

<b>Product Code</b>	FLW66
<b>Product Details</b>	A semi gloss white, one side coated, lightweight, calendered, woodfree printing paper. This paper provides excellent print quality by all the usual printing techniques.
<b>Face Material</b>	
Description	coated woodfree paper
Finish and Colour	Semi Gloss White
Weight / Thickness	62 gsm / 55 micron
<b>Adhesive</b>	
Type	S660, Permanent, Acrylic
Minimum Application Temp	10 °C
In Service Temp	-20 °C to +80 °C
Initial Tack	High
Ultimate Adhesion	Very High
Notes	The adhesive can be used in direct contact with dry, non fatty foodstuffs Complies with the European Food Directives FDA 175.105 and German Recommendations XIV as published by BfR.
<b>Release Liner</b>	
Weight	74 gsm
Colour	BG45 White, supercalendered glassine
Thickness	63 micron
<b>Application</b>	Labels for use in the cosmetic and pharmaceutical industry. Very good for small cylindrical or curved substrates.
<b>Shelf Life</b>	2 years

We reserve the right to supply comparable materials against any product without prior notice. The values given are typical, the information being given in good faith but without warranty. All goods are supplied in accordance with our Standard Terms and Conditions of Sale, and no recommendations for specific application or use are given. The user must satisfy themselves as to the suitability of a particular grade for their own application.

Ref :- 038

**t:0161 343 1131 w:www.magnum-uk.com e:sales@magnum-uk.com**

MAGNUM MATERIALS LTD, THE SELF ADHESIVE CENTRE Globe Lane Industrial Estate, Dukinfield, Cheshire SK16 4UG