



Specification

Fastuff

Product Code FTUF

Product Details A matt clay, coated HDPE film designed for use in very difficult application areas. The clay coated film give a good balance for printability with most common variable imprint techniques, notably thermal transfer, dot matrix, bold inkjet and cold laser.

Face Material

Description HDPE film
Finish and Colour Matt white
Weight / Thickness 90 gsm / 110 micron

Adhesive

Type Permanent, Rubber
Minimum Application Temp -5 °C
In Service Temp -40 °C to 70 °C
Initial Tack High
Ultimate Adhesion Very High
Notes Complies with European food directives and legislations, FDA 175.105 and the German XXI as published by BfR. Can be used in direct contact with dry & moist Non Fatty foodstuffs. Also BS5609 Part II (Labels for Marine Use) approved.

Release Liner

Weight 59 gsm
Colour BG40 Brown, supercalendered glassine
Thickness 53 micron

Application Shrink wrapped pallets to timber, rough metal castings and rough LDPE drums.

Shelf Life 2 years

We reserve the right to supply comparable materials against any product without prior notice. The values given are typical, the information being given in good faith but without warranty. All goods are supplied in accordance with our Standard Terms and Conditions of Sale, and no recommendations for specific application or use are given. The user must satisfy themselves as to the suitability of a particular grade for their own application.

Ref :- 038

t:0161 343 1131 w:www.magnum-uk.com e:sales@magnum-uk.com

MAGNUM MATERIALS LTD, THE SELF ADHESIVE CENTRE Globe Lane Industrial Estate, Dukinfield, Cheshire SK16 4UG