



Specification

Tyvek Perm

| | |
|--------------------------|--|
| Product Code | TYP |
| Product Details | A White, durable nonwoven, 100% polyethylene fibres. Extremely tear resistant. Highly resistant to weather, suitable for outdoor use. Offers excellent quality using traditional printing methods. Corresponds to BfR III. |
| Face Material | |
| Description | Polyethylene |
| Finish and Colour | Nonwoven White |
| Weight / Thickness | 75 gsm / 205 micron |
| Adhesive | |
| Type | Permanent, Acrylic |
| Minimum Application Temp | 5 °C |
| In Service Temp | -30°C to 120 °C |
| Initial Tack | High |
| Ultimate Adhesion | High |
| Notes | Excellent adhesion on various surfaces. High adhesion on both polar and nonpolar (PE) surfaces. Highly waterproof and particularly resistant to light, heat and ageing. Complies with FDA 21 CFR 175.105 |
| Release Liner | |
| Weight | 59 gsm |
| Colour | White glassine |
| Thickness | 52 micron |
| Application | Weather resistant, suitable for outdoor use. Suitable for labels requiring a high degree of tensile strength. |
| Shelf Life | 4 years |

We reserve the right to supply comparable materials against any product without prior notice. The values given are typical, the information being given in good faith but without warranty. All goods are supplied in accordance with our Standard Terms and Conditions of Sale, and no recommendations for specific application or use are given. The user must satisfy themselves as to the suitability of a particular grade for their own application.

Ref :- 240

t:0161 343 1131 w:www.magnum-uk.com e:sales@magnum-uk.com

MAGNUM MATERIALS LTD, THE SELF ADHESIVE CENTRE Globe Lane Industrial Estate, Dukinfield, Cheshire SK16 4UG