



Specification

Tyre Label Perm

Product Code

TYRE

Product Details

A semi gloss paper laminated to a 7 micron aluminium barrier foil.
This paper provides excellent print quality by all the usual printing techniques including thermal transfer.

Face Material

Description Coated paper
Finish and Colour Semi gloss White
Weight / Thickness 100 gsm / 80 micron

Adhesive

Type Extra Permanent, Hot Melt
Minimum Application Temp 0 °C
In Service Temp -20 °C to +60 °C
Initial Tack Very High
Ultimate Adhesion Very High
Notes Complies with requirements of indirect food additive regulation 21 CFR-175.105 "Adhesive" The complies with the Bfr XIV regulations for direct contact with dry and moist non-fatty foodstuffs ISEGA certificate No. 31790 U 11

Release Liner

Weight 62 gsm
Colour Honey glassine
Thickness 55 micron

Application

Tyres, Fruit labelling, Metal Detectable applications and other applications include rough, contoured surfaces.

Shelf Life

1 year

We reserve the right to supply comparable materials against any product without prior notice. The values given are typical, the information being given in good faith but without warranty. All goods are supplied in accordance with our Standard Terms and Conditions of Sale, and no recommendations for specific application or use are given. The user must satisfy themselves as to the suitability of a particular grade for their own application.

Ref :- 142

t:0161 343 1131 w:www.magnum-uk.com e:sales@magnum-uk.com

MAGNUM MATERIALS LTD, THE SELF ADHESIVE CENTRE Globe Lane Industrial Estate, Dukinfield, Cheshire SK16 4UG