



Specification

Fastyre

Product Code TYRL

Product Details A white, woodfree, printing paper with semi gloss appearance laminated to a flexible aluminium barrier foil.
The aluminium barrier foil prevents migration of components through to the face stock thus avoiding the label from getting stained.
Printing can be done in all applicable label printing technologies.

Face Material

Description Paper with foil barrier
Finish and Colour Semi gloss white
Weight / Thickness 82 gsm / 60 micron

Adhesive

Type TS79, Permanent, Rubber
Minimum Application Temp -0 ° C
In Service Temp -20 °C to 70 °C
Initial Tack Very High
Ultimate Adhesion Very High
Notes Highly aggressive adhesive is specially designed for use on difficult and rough substrates such as tyres.

Release Liner

Weight 78 gsm
Colour BG50 White, supercalendered glassine
Thickness 68 micron

Application Automotive tyre labelling

Shelf Life 1 year

We reserve the right to supply comparable materials against any product without prior notice. The values given are typical, the information being given in good faith but without warranty. All goods are supplied in accordance with our Standard Terms and Conditions of Sale, and no recommendations for specific application or use are given. The user must satisfy themselves as to the suitability of a particular grade for their own application.

Ref :- 038

t:0161 343 1131 w:www.magnum-uk.com e:sales@magnum-uk.com

MAGNUM MATERIALS LTD, THE SELF ADHESIVE CENTRE Globe Lane Industrial Estate, Dukinfield, Cheshire SK16 4UG